

COUNTERFEITER SUSPECTS ARE NABBED IN RAID

Equipment and Fake Bills Seized, Police Say; Two Arrested.

Battering their way into the hideout and plant of Frank Kuczynski, 54, of 726 West Vermont street, alleged nationally sought counterfeiter, detectives and police Tuesday night arrested him and a confederate.

Large quantities of dies, engraving oils, chemicals, a printing press and other equipment for making counterfeit money and several hundred fake \$100 bills were confiscated.

Kuczynski and his son, E. Oliver, 18, of Providence, R. I., were to be arraigned before a United States commissioner today.

Tried to Pass "Queer" Bills

Oliver, who said he was a Negro, but had been passing for a white man, was arrested after police said he had attempted to pass the counterfeit bills in Military park.

Fred S. Loggins, federal secret service operative, said he had pursued Kuczynski half way across the continent.

In a statement to detectives, the alleged counterfeiter is said to have admitted he started work on 900 of the \$10 bills in the east after purchasing the equipment in New York. Kuczynski said he had planned manufacture of the bills at Milwaukee several months ago.

The alleged leader of the ring, several agents of which are sought, is said to have asked to plead guilty in federal court.

Served Prison Term

Loggins said Kuczynski had been released from the Leavenworth federal penitentiary last March after he had completed service of a ten-year sentence on a similar charge.

Oliver said he had met Kuczynski in Jersey City and the latter had promised him they would "make a lot of money."

Kuczynski refused to admit detectives and Loggins into his room when they demanded entrance and it was necessary to smash the door to get to the plants.

Majority of the fake money, detectives said, was found in an accordion in one of the two rooms in which the equipment was kept.

STONE STRIKES BABY

Parents of Boy Rock-Hurters Notified by Police.

One of several boys playing near Keeling avenue and Pratt street late Tuesday hurled a rock that struck a 9-months-old baby on the head.

The child was Betty Tout, daughter of Mrs. George Tout, 3535 East Vernon street, who was carrying the baby when the stone hit her. The injury was not serious. The boys ran, but their names were obtained and their parents notified by police.

Gone, but Not Forgotten

Automobiles reported to police as stolen belong to: Gaston Criss, 2755 Bellefontaine street, Indianapolis, from rear of 2755 Bellefontaine street; John Ostermeier, 1527 East Southern avenue; Ford roadster, 87-894, from Shady and Orange streets.

BACK HOME AGAIN

Stolen automobile recovered by police belong to: Frank Carr, Sheridan, Ind., Chevrolet coupe, found in front of 6558 College avenue; Sylvester Power, 913 South New Jersey street; Ford coupe, found at Bickling and Hill streets; Karl Kaiser, 575 North Delaware street, Marion; 1930 Ford, found at Fifteenth street and Cornell avenue; Orville Hinshaw, 3415 Arden avenue, Indianapolis, rear of 2045 North Keystone avenue; 1930 Ford, Concord street, Cheverlet roadster, found at Fletcher avenue and East street; John B. Behnke, 2162 Hawthorne Lane, Ford coach, found in front of 230 North New Jersey street.

Don't be Constipated

GOOD news for those who suffer from sour stomach, constipation and that "morning after" feeling! French Lick Salts—pleasant-tasting newsaline from French Lick Springs—brings sure, quick relief.

Even in stubborn cases, where other laxatives fail, French Lick Salts gives prompt results. Everyone knows that the saline type of laxative is best. Now you can enjoy taking a saline. Just drop a little French Lick Salts in cool water. It effervesces merrily. Drink it down—it's as delightful as a fountain beverage!

French Lick Salts is a skillful blend of the same health-giving mineral salts found in the renowned spring waters at famous French Lick Springs—combined in effervescent form. It cleans the tract by washing, just as do the waters at French Lick.

French Lick Salts will not gripe. It is gentle and pleasant though prompt and complete. Its effect is to heal and soothe. Your druggist has French Lick Salts—a generous bottle for 50 cents. Try it today.

French Lick Salts

THE PLEASANT EFFERVESCENT LAXATIVE

Quick, Accurate Optical Work

Hoosier Optical Co. 144 N. Illinois St.

Insulated Furnace Pipes Bring Marked Saving in Coal Bills

This is the first of a series of weekly articles on the preparation of the home for winter.

By NEA Service
WASHINGTON, Sept. 9.—The fast approach of winter and the growing tendency of home owners to do their own repairing in preparation against the cold weather have led various government departments here to prepare information that will guide these home owners properly in to remedy this.

It is a good plan to clean the chimney of its accumulated soot at least once a year. If this is done, a good draft will result and perfect checking of the fire can be accomplished.

The cheapest way of doing this is to throw three or four handfuls of common salt in the fire box in which a hot fire is blazing.

If not salt, zinc scrapings or some old dry batteries can be thrown in with the fire under full draft.

The fumes carried up the chimney at a terrific speed tear loose the sooty deposit, carrying some out the top of the chimney, and causing the rest to drop to the bottom.

After the heat-making end of the furnace has been examined and all of the flaws repaired, next go over the heat-dispensing units.

First, these authorities say, the furnace must be just the right size for the home. If it's too large, it will waste coal. If too small, it won't heat the house well enough.

A furnace man can advise whether the unit is large enough, or it might be compared with a neighbor's furnace, where heating is to be efficient.

The furnace should be cleaned out thoroughly.

After removing the ashes, close the doors and dampers. Then open the part marked "Clean Out" and with a vacuum cleaner or a brush on the end of a long wire, remove the thin dust, scraping vigorously every bit of the surface within reach. The dust will work downward into the ash pit.

Then clean the smoke pipe that leads into the chimney. Take it down and remove all the soot from it. Fit it back snugly, filling around the intersection with cement or asbestos packing.

The firepot itself requires a close examination. Cracks in it will make a lot of trouble. They should be repaired with firepot paste or putty. Broken or warped grates also should be replaced.

The chimney, according to the United States department of commerce, is sometimes responsible for a lot of waste heat. It may be too

small for its height, leaky, obstructed outside, affected by prevailing winds which sweep over the top of the house and down into it, or a dozen other things may affect it.

If the chimney is faulty, and has shown a tendency to give an improper draft in the past, a heating specialist should be called in to remedy this.

It is a good plan to clean the chimney of its accumulated soot at least once a year. If this is done, a good draft will result and perfect checking of the fire can be accomplished.

The cheapest way of doing this is to throw three or four handfuls of common salt in the fire box in which a hot fire is blazing.

If not salt, zinc scrapings or some old dry batteries can be thrown in with the fire under full draft.

The fumes carried up the chimney at a terrific speed tear loose the sooty deposit, carrying some out the top of the chimney, and causing the rest to drop to the bottom.

After the heat-making end of the furnace has been examined and all of the flaws repaired, next go over the heat-dispensing units.

First, these authorities say, the furnace must be just the right size for the home. If it's too large, it will waste coal. If too small, it won't heat the house well enough.

A furnace man can advise whether the unit is large enough, or it might be compared with a neighbor's furnace, where heating is to be efficient.

The furnace should be cleaned out thoroughly.

After removing the ashes, close the doors and dampers. Then open the part marked "Clean Out" and with a vacuum cleaner or a brush on the end of a long wire, remove the thin dust, scraping vigorously every bit of the surface within reach. The dust will work downward into the ash pit.

Then clean the smoke pipe that leads into the chimney. Take it down and remove all the soot from it. Fit it back snugly, filling around the intersection with cement or asbestos packing.

The firepot itself requires a close examination. Cracks in it will make a lot of trouble. They should be repaired with firepot paste or putty. Broken or warped grates also should be replaced.

The chimney, according to the United States department of commerce, is sometimes responsible for a lot of waste heat. It may be too

small for its height, leaky, obstructed outside, affected by prevailing winds which sweep over the top of the house and down into it, or a dozen other things may affect it.

If the chimney is faulty, and has shown a tendency to give an improper draft in the past, a heating specialist should be called in to remedy this.

It is a good plan to clean the chimney of its accumulated soot at least once a year. If this is done, a good draft will result and perfect checking of the fire can be accomplished.

The cheapest way of doing this is to throw three or four handfuls of common salt in the fire box in which a hot fire is blazing.

If not salt, zinc scrapings or some old dry batteries can be thrown in with the fire under full draft.

The fumes carried up the chimney at a terrific speed tear loose the sooty deposit, carrying some out the top of the chimney, and causing the rest to drop to the bottom.

After the heat-making end of the furnace has been examined and all of the flaws repaired, next go over the heat-dispensing units.

First, these authorities say, the furnace must be just the right size for the home. If it's too large, it will waste coal. If too small, it won't heat the house well enough.

A furnace man can advise whether the unit is large enough, or it might be compared with a neighbor's furnace, where heating is to be efficient.

The furnace should be cleaned out thoroughly.

After removing the ashes, close the doors and dampers. Then open the part marked "Clean Out" and with a vacuum cleaner or a brush on the end of a long wire, remove the thin dust, scraping vigorously every bit of the surface within reach. The dust will work downward into the ash pit.

Then clean the smoke pipe that leads into the chimney. Take it down and remove all the soot from it. Fit it back snugly, filling around the intersection with cement or asbestos packing.

The firepot itself requires a close examination. Cracks in it will make a lot of trouble. They should be repaired with firepot paste or putty. Broken or warped grates also should be replaced.

The chimney, according to the United States department of commerce, is sometimes responsible for a lot of waste heat. It may be too

small for its height, leaky, obstructed outside, affected by prevailing winds which sweep over the top of the house and down into it, or a dozen other things may affect it.

If the chimney is faulty, and has shown a tendency to give an improper draft in the past, a heating specialist should be called in to remedy this.

It is a good plan to clean the chimney of its accumulated soot at least once a year. If this is done, a good draft will result and perfect checking of the fire can be accomplished.

The cheapest way of doing this is to throw three or four handfuls of common salt in the fire box in which a hot fire is blazing.

If not salt, zinc scrapings or some old dry batteries can be thrown in with the fire under full draft.

The fumes carried up the chimney at a terrific speed tear loose the sooty deposit, carrying some out the top of the chimney, and causing the rest to drop to the bottom.

After the heat-making end of the furnace has been examined and all of the flaws repaired, next go over the heat-dispensing units.

First, these authorities say, the furnace must be just the right size for the home. If it's too large, it will waste coal. If too small, it won't heat the house well enough.

A furnace man can advise whether the unit is large enough, or it might be compared with a neighbor's furnace, where heating is to be efficient.

The furnace should be cleaned out thoroughly.

After removing the ashes, close the doors and dampers. Then open the part marked "Clean Out" and with a vacuum cleaner or a brush on the end of a long wire, remove the thin dust, scraping vigorously every bit of the surface within reach. The dust will work downward into the ash pit.

Then clean the smoke pipe that leads into the chimney. Take it down and remove all the soot from it. Fit it back snugly, filling around the intersection with cement or asbestos packing.

The firepot itself requires a close examination. Cracks in it will make a lot of trouble. They should be repaired with firepot paste or putty. Broken or warped grates also should be replaced.

The chimney, according to the United States department of commerce, is sometimes responsible for a lot of waste heat. It may be too

small for its height, leaky, obstructed outside, affected by prevailing winds which sweep over the top of the house and down into it, or a dozen other things may affect it.

If the chimney is faulty, and has shown a tendency to give an improper draft in the past, a heating specialist should be called in to remedy this.

It is a good plan to clean the chimney of its accumulated soot at least once a year. If this is done, a good draft will result and perfect checking of the fire can be accomplished.

The cheapest way of doing this is to throw three or four handfuls of common salt in the fire box in which a hot fire is blazing.

If not salt, zinc scrapings or some old dry batteries can be thrown in with the fire under full draft.

The fumes carried up the chimney at a terrific speed tear loose the sooty deposit, carrying some out the top of the chimney, and causing the rest to drop to the bottom.

After the heat-making end of the furnace has been examined and all of the flaws repaired, next go over the heat-dispensing units.

First, these authorities say, the furnace must be just the right size for the home. If it's too large, it will waste coal. If too small, it won't heat the house well enough.

A furnace man can advise whether the unit is large enough, or it might be compared with a neighbor's furnace, where heating is to be efficient.

The furnace should be cleaned out thoroughly.

After removing the ashes, close the doors and dampers. Then open the part marked "Clean Out" and with a vacuum cleaner or a brush on the end of a long wire, remove the thin dust, scraping vigorously every bit of the surface within reach. The dust will work downward into the ash pit.

Then clean the smoke pipe that leads into the chimney. Take it down and remove all the soot from it. Fit it back snugly, filling around the intersection with cement or asbestos packing.

The firepot itself requires a close examination. Cracks in it will make a lot of trouble. They should be repaired with firepot paste or putty. Broken or warped grates also should be replaced.

The chimney, according to the United States department of commerce, is sometimes responsible for a lot of waste heat. It may be too

small for its height, leaky, obstructed outside, affected by prevailing winds which sweep over the top of the house and down into it, or a dozen other things may affect it.

If the chimney is faulty, and has shown a tendency to give an improper draft in the past, a heating specialist should be called in to remedy this.

It is a good plan to clean the chimney of its accumulated soot at least once a year. If this is done, a good draft will result and perfect checking of the fire can be accomplished.

The cheapest way of doing this is to throw three or four handfuls of common salt in the fire box in which a hot fire is blazing.

If not salt, zinc scrapings or some old dry batteries can be thrown in with the fire under full draft.

The fumes carried up the chimney at a terrific speed tear loose the sooty deposit, carrying some out the top of the chimney, and causing the rest to drop to the bottom.

After the heat-making end of the furnace has been examined and all of the flaws repaired, next go over the heat-dispensing units.

First, these authorities say, the furnace must be just the right size for the home. If it's too large, it will waste coal. If too small, it won't heat the house well enough.

A furnace man can advise whether the unit is large enough, or it might be compared with a neighbor's furnace, where heating is to be efficient.

The furnace should be cleaned out thoroughly.

After removing the ashes, close the doors and dampers. Then open the part marked "Clean Out" and with a vacuum cleaner or a brush on the end of a long wire, remove the thin dust, scraping vigorously every bit of the surface within reach. The dust will work downward into the ash pit.

Then clean the smoke pipe that leads into the chimney. Take it down and remove all the soot from it. Fit it back snugly, filling around the intersection with cement or asbestos packing.

The firepot itself requires a close examination. Cracks in it will make a lot of